


PCB LAYOUT

SPECIFICATIONS

Current Rating :1.5AMP
 Operation Temperature:-40°C to+105°C
 Contact Resistance :20m Max.
 Insulation Resistance:1000M Mhm.
 Withstanding Voltage :AC 500V

PART NO:2PH-2060-SMD

□表示PIN脚数2-40



B	CONTACT	2-40	BRASS	Au or Sn Over 50u" Ni
A	HOUSING	1	Polyester(ULE 94V-0) Standard Nylon-6T	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
3G ENTERPRISE LIMITED				
DECIMALS: ANGLES:				
X	:±0.35			
.X	:±0.25			
.XX	:±0.20			
.XXX	:±0.15			
TITLE	PH2.0 2X排 L=8.3(6.3(0.2)/6.0 SMT			
DWN	JACK	PART NO:	2PH-2060-SMD	
CHKD	SCALE:	UNIT:	mm	
APVD	SIZE: A3	SHEET: 1OF 1	REV: A	

CUSTOMER COPY

1 2 3 4 5

1 2 3 4 5

6 7 8

6 7 8