



规格说明: Specifications:  
电气特性: Electrical:

- 1. 额定电流: Current Rating  
1.5A/contact terminal
- 2. 额定电压: Voltage Rating  
30V DC
- 3. 接触阻抗: Contact Resistance  
30 milliohms MAX
- 4. 耐电压: Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
- 5. 绝缘阻抗: Insulation Resistance:  
1000MEGA ohms MIN

物理性能: Mechanical:

- 1. 插拔力: Connector Mate and Unmate Force  
Mate force: 3.57kgf (MAX)  
Unmate force: 1.02kgf (MIN)
- 2. 端子保持力: Terminal Retention  
1.2kgf (MIN)

原材料: Material:

- 1. 塑胶: Housing:  
Hing Temperature Thermoplastics,  
Ul 94V-0 LCP White/Black
- 2. 端子: Contact: C2680
- 3. 外壳: Shell: C2680/SPCC

电镀: Finish:

- 1. 端子: Contact: Plated Gold in Mating Area;  
Tin On Solder Tails
- 2. 外壳: Shell:  
Nickel Plating

REV.	ECN NO.	MODIFY CONTENT	DATE
A		NEW	2012/04/13

GENERAL TOLERANCE		DWG NO.	APPD:	WIND	Scale
X $\pm 0.45$	X $\pm 5^{\circ}$	JYSA0804-001			1:1
X $\pm 0.35$	X $\pm 2^{\circ}$	Title	CHKD:		UNIT
		USB A/F 180° SMT 柱L.0 直边	DR:		mm
XX $\pm 0.25$	.XX $\pm 1^{\circ}$	Part NO.	Date		
.XXX $\pm 0.15$	.xxx $\pm 0.5^{\circ}$	JYS-USB700-015	2012/04/13		
SHEET 1/1					


 杰宇森电子有限公司  
 JIE YU SEN ELECTRONIC CO., LTD.